



# EVO-STIK Sticks Like Sh\*t Sealant

## NO COMPROMISE WATERPROOF SEALANT

Date: 17 August 2017

Fact Sheet No.: TDS00111

### YOUR SMART ADVANTAGES

- Ultra flexible no compromise sealant
- Sticks to wet surfaces
- Mould Resistant & overpaintable when dry

### USES

Ideal for most sealing jobs, indoors and outdoors. Use in bathrooms and kitchens, sealing around window and door frames. Can be used for sealing roof and guttering, even when it's raining.

Bonds to most surfaces including wood, concrete, brick, plaster, glass, ceramics, metals, rigid PVC, GRP, insulation boards and foam polystyrene. Not suitable for glazing.

### PRODUCT CHARACTERISTICS

Colour	Clear
Form	Soft gunnable paste
Specific Gravity	1.05 at 23°C and 50% relative humidity
Composition	One component elastic sealant based upon silyl modified polymers.
Product Code	30811716 Sticks Like Sh*t C20 x 12 30814543 Sticks Like C20 x 12
Storage/Shelf Life	12 months from the date of manufacture when stored in the dry between +5°C & +25°C, out of direct sunlight. Protect from frost.

### TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +40°C
Service Temperature	-40°C to +80°C
Coverage	Approx. 10 linear metres of 6mm diameter bead per C20 cartridge
Drying Times	Skin Formation: 15 - 30 minutes, dependent on ambient conditions.  Through Dry: Approx. 2-3mm per 24 hours at 23°C and 50% relative humidity. Fully dry in approx. 1-2 days depending on bead width, temperature and humidity.  Always tool sealant within 10 minutes of application.
Shore A Hardness	50 - 55
Tensile Strength	1.5 - 1.8 MPA at 100% extension
Elongation at Break	200 - 300%
Movement	Will accommodate up to ±15% of the mean joint width

### DIRECTIONS FOR USE

#### Important

Before using EVO-STIK Sticks Like Sealant refer to the relevant Health & Safety Data Sheet. Available at [www.bostik.co.uk](http://www.bostik.co.uk) named as the code above.

### PREPARATION



FM 01696  
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 [www.bostik.co.uk](http://www.bostik.co.uk)

Bostik, EVO-STIK & Sealocrete are registered trademarks of Bostik Ltd.

1. Work in warm but well ventilated conditions.
2. Joint surfaces must be clean, dry, sound and free from dust and other contaminants that may impair adhesion.
3. If desired place masking tape along the joint edges before application. This can make it easier to make a neat, tooled finish. Use a spatula with a round end to tool the sealant and check that this tool just fits into the gap between the masking tape so that it catches the excess sealant.
4. Do a test run without applying any sealant to 'get a feel' for the difficult areas to seal in corners, behind taps and raised joints.

#### APPLICATION

1. Unscrew the nozzle, and using a sharp knife, cut off the dome of the cartridge, taking care not to damage the thread. Screw the nozzle onto the cartridge.
2. Cut off the tapered end of the nozzle at a 45° angle, to a width matching the gap to be sealed.
3. Fit the cartridge into the cartridge gun by pressing the release plate and pulling out the plunger. Insert cartridge and repeatedly squeeze the trigger until the sealant appears.
4. Place the nozzle at the start of the gap, and gently squeeze the trigger. Push forward slowly, ensuring that contact is made by the sealant with both sides of the gap. At the end of the run, release the trigger and press the plunger release plate of the gun.
5. Sealant must be gunned firmly into the joints to ensure good adhesion to the joint surfaces.
6. Smooth the sealant with a wet, round ended tool (do not use a wetted finger), remove any excess with a cloth moistened with white spirit and then remove the masking tape from either side of the bead.
7. After use, ensure the cap is replaced to prevent nozzle from clogging.
8. The sealant skins over rapidly (approx. 15-30 minutes) and is fully cured in 1-2 days depending on bead width, temperature and humidity.

#### CLEANING

1. **Uncured Sealant.**  
The bulk should be removed carefully using a soft scraper. The remainder can be removed using a cloth just moistened with white spirit. Repeat using another clean cloth moistened with white spirit.
2. **Cured sealant**  
There is no adequate solvent; carefully cut away excess with a very sharp knife. Do not use solvent to remove product from skin – use soap and water.

#### PRECAUTIONS IN USE

1. EVO-STIK Sticks Like Sealant will not resist abrasion in floor joints. Do not use in swimming pools. Do not use for aquarium applications. Do not use on or near bitumen. Do not use for bedding in double glazed/insulating glass units into frames. Do not submerge under water. Will not bond polypropylene, polyethylene or Teflon. Prevent entry of uncured sealant into drains or watercourses. The sealant is overpaintable after 24 hours with most paints (avoid alkyd resin based paints). A test should be done on a small surface first to check compatibility.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.co.uk](http://www.bostik.co.uk) for advice.

For health and safety instructions, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK Sticks Like Sealant.



FM 01696  
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 [www.bostik.co.uk](http://www.bostik.co.uk)

Bostik, EVO-STIK & Sealocrete are registered trademarks of Bostik Ltd.

**CONSTRUCTION PRODUCT REGULATION  
DECLARATION OF PERFORMANCE**

Product Description: **EVO-STIK Sticks Like Sh\*t Sealant, EVO-STIK Sticks Like Sealant**

Product Code: **5000403110011, 5000403113340**

Intended Use: **Façade and Sanitary Sealant**

Manufacturer: **Bostik Ltd**

Contact Address: **Common Road  
Stafford  
ST16 3EH**

System of Assessment: **System 3**

Harmonised Standard: **BS EN 15651-1,3:2012**

Notified Body: **0074**

Declared Performance:

Essential Characteristics	Performance	
Reaction to Fire	F	
Release of Chemicals	None	See safety data sheet
Resistance to Flow	≤3mm	BS EN 15651-1,3
Loss of Volume	NPD	
Tensile properties after immersion in water at 23°C*	≥25%	BS EN 15651-1,3
Tensile properties at maintained extension after immersion in water at 23°C*	NF	BS EN 15651-1,3
Microbiological Growth	NPD	BS EN 15651-3
Durability	NPD	BS EN 15651-1,3

**\*Conditioning method A, tested on Aluminium Substrate, no prime**


The performance of the EVO-STIK Sticks Like Sealant, EVO-STIK Sticks Like Sh\*t Sealant, 5000403110011, 5000403113340 is in conformity with the declared performance shown in the table above.

This declaration of performance is issued under the sole responsibility of Bostik Ltd.

**Signed for and on behalf of Bostik Ltd by:**

**Name:** Alison Jamieson

**Function:** S.H.E.Q. Manager

**Signature:** 

**Date:** June 2014



FM 01696  
BS EN ISO 9001:2008



FM 01696  
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 [www.bostik.co.uk](http://www.bostik.co.uk)  
Bostik, EVO-STIK & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	<a href="mailto:stafford.gatehouse@bostik.com">stafford.gatehouse@bostik.com</a>



FM 01696  
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 [www.bostik.co.uk](http://www.bostik.co.uk)  
Bostik, EVO-STIK & Sealocrete are registered trademarks of Bostik Ltd.