



Flashband Primer S.V.

FOR ROOFS

Date: 06 January 2016

Fact Sheet No.: TDS00039

YOUR SMART ADVANTAGES

- Quick dry, cold weather formula
- Improves grab and adhesion
- Porous, rough, dusty or damp surfaces

USES

Bostik Flashband Primer S.V. for Roofs is a solvent borne bitumen solution, for priming/sealing brickwork, cement renderings, roof tiles, concrete, mineralised felt, timber, metal, rainwater pipes, gutters and corrugated sheeting. It is also ideal to use prior to the application of other bitumen products and particularly where there are porous or dusty surfaces.

Use Bostik Flashband Primer S.V. for Roofs before applying Bostik Self Adhesive Flashing Tape to porous or dusty surfaces in damp or cold weather.

PRODUCT CHARACTERISTICS

Colour	Black
Form	Low viscosity liquid
Specific Gravity	0.9 approx.
Composition	Solution of bitumen solvent
Product Codes	30812257 500ml x 12 30812258 1 litre x 12
Storage/Shelf Life	Store and transport this container in a secure upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +30°C and out of direct sunlight.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +35°C
Service Temperature	-10°C to +70°C
Coverage	7 - 9m ² per litre, depending on porosity of surface
Solvent for Cleaning Up	White Spirit

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Flashband Primer S.V. for Roofs refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Ensure the roof surface is structurally sound, clean, dry and free from surface contaminants such as grease, oil, rust and dirt.
2. Remove any organic growth i.e. moss or lichen with Bostik Fungicidal Wash.

APPLICATION

3. Apply Bostik Flashband Primer S.V. for Roofs with a soft bristle brush and allow to dry before over coating with Bostik Flashband or other bitumen products. Where possible we recommend using disposable brushes for the application of Bostik Flashband Primer S.V. for Roofs.

CLEANING

4. Clean tools and equipment immediately after use with white spirit.
5. Dried product is difficult to remove.
6. Use proprietary hand cleaners for splashes on skin. Do not use solvents.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

PRECAUTIONS IN USE

Do not use over tar based products. Do not use if the surface temperature is likely to rise above 65°C. Do not allow the primer to be applied on or near to silicones of any kind. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Colour indicated on pack is a guide only. It is recommended that users apply a small amount of Bostik Flashband Primer S.V. for Roofs in an inconspicuous area and allow to dry to determine colour suitability before commencing work. Shade variations may occur between batches. When completing projects requiring multiple tins please ensure that they are from the same batch.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Flashband Primer S.V, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.