



## EVO-STIK 528 KONTAKTL ME

Visp r ja pielietojuma polihloropr na l me

Tehnisk lapa Nr.: TDS00442 (08/01/2024)

### GALVEN S PRIEKŠROC BAS

- ✓ Augsta s kotn j sa ere un izcila gal j savienojuma stipr ba
- ✓ Augsta b des iztur ba un laba temperat ras notur ba
- ✓ Viegla uzkl šana, izmantojot robaino šp teli.

### APRAKSTS

EVO-STIK 528 kontaktl me ir paredz ta lietošanai **iekštelp s**. To var izmantot ar ra apst k os, ja t ir aizsarg ta no laikapst k u ietekmes (saules un lietus), piem ram, l m jot lamin tus.

L me ir gatava lietošanai un savieno:

- ✓ Dekorat vos lamin tus (piem ram, Formica), cieto PVH, koku, skaidu pl tnes, kokš iedras pl tnes, kor i, du, dažus gumijas veidus, akmeni, met lu un bl vus, stingrus audumus.
- ✓ To var izmantot ar izol cijas š iedru pl t u un akustisko fl žu l m šanai pie piekaram m vai vertik l m virsm m (griestiem vai sien m).

**BR DIN JUMS:** Neizmantoj uz polistirola (putuplasta) vai celulozes kr sot m virsm m



### TEHNISKIE RAKSTURLIELUMI

Kr sa	Dzintara
Forma	Viskozs š idrums
Bl vums	0.84 aptuveni
Sast vs	Polihloropr na gumijas un sint tisko sve u mais jums naftas b zes š din t jos
Uzkl šanas temperat ra	+5°C to +30°C
Ž šanas laiks	Putek u drošs (sauss uz tausti) 10–20 min t s. Pilna stipr ba tiek sasniegta 24 stund s
Atv rtais laiks	L dz pat 45 min tes
Pat ri š (aptuveni)	4-6m <sup>2</sup> ar litru vien k rt , (atkar b no virsmas veida)

### LIETOŠANAS INSTRUKCIJA

**SVAR GI:** Pirms EVO-STIK 528 kontaktl mes lietošanas skatiet attiec go vesel bas aizsardz bas un droš bas datu lapu, kas pieejama vietn [www.bostik.co.uk](http://www.bostik.co.uk).

#### SAGATAVOŠANA

- Virsmas j b t saus m, t r m un br v m no putek iem, net rumiem un taukiem.
- Gludas vai pul tas virsmas j padara raupjas ar smalku abraz vu.
- Attaukošanai vispirms apsveriet dens/mazg šanas l dzek a š dumu. Ja tas nav piem rots, izmantojiet š din t ju, piem ram, EVO-STIK Adhesive Cleaner.
- Pirms attaukošanas p rbaudiet š din t ja ietekmi uz plastmasu, gumiju vai kr sot m virsm m.
- Pirms l mes uzkl šanas visiem š din t ja tvaikiem ir piln b j izgaro

#### UZKL ŠANA

- ✓ Uzkl jiet vienm r gu, rievotu l mes k rtu uz ab m l m jam m virsm m, izmantojot robaino šp teli.
- ✓ Uzkl jiet vienm r gu, rievotu l mes k rtu uz ab m l m jam m virsm m, izmantojot robaino šp teli.
- ✓ Izmantojiet šp teli vai izklid t ju ar robainu malu.

- ✓ P rliecinieties, ka šp teles robi nav nodiluši vai aizpild ti ar sakaltušu l mi.
- ✓ Lai nodrošin tu pareizu pat ri u, turiet šp teli t d le , kas p c nož šanas veido izteiktu rievojumu
- ✓ Turiet virsmas atseviš i, l dz abas l mes k rtas ir k uvušas sausas uz tausti.  
Piez me: Āugsta mitruma apst k os uz l mes var par d ties balta apsarme. Š d gad jum darbu nedr kst turpin t, kam r apst k i neuzlabojas (paaugstinot temperat ru vai sausinot gaisu).
- ✓ Parasti ž šanas laiks ir 10–15 min tes porain m virsm un 10–20 min tes neporain m virsm m.
- ✓ Savienošānu nevajadz tu atlikt ilg k par 45 min t m p c uzkl šanas.
- ✓ Savietojiet abas virsmas un saspiediet t s kop vis laukum .
- ✓ Pietiek ar rokas spiedienu, ta u ieteicams izmantot gumijas rull ti vai presi. Nepieciešams notur gs spiediens.
- ✓ S kotn j stipr ba auj deta as lietot nekav joties, bet maksim l stipr ba tiek sasniegta p c 24–48 stund m.
- S kotn j savienojuma stipr ba auj nekav joties turpin t darbu ar sal m to konstrukciju, ta u maksim l savienojuma stipr ba tiek sasniegta p c aptuveni 24 l dz 48 stund m norm l temperat r .
- Ja pl notais lietošanas veids šeit nav min ts, sazinieties ar tehnisko pakalpojumu noda u pa t lruni +44 (0)1785 272625 vai apmekl jiet vietni [www.bostik.co.uk](http://www.bostik.co.uk).
- ✓ Ieteikumi un priekšlikumi ir sniegti tikai informat vos nol kos, jo lietošanas apst k i piln b atrodas rpus m su kontroles.
- ✓ Vesel bas aizsardz bas un droš bas instrukcijas, pirm s pal dz bas pas kumus, k ar nor d jumus par nopl žu nov ršanu un likvid šānu skatiet atseviš EVO-STIK 528 kontaktl mes droš bas datu lap , kas pieejama vietn [www.Erkulis.lv](http://www.Erkulis.lv)

## TR ŠANA

- ✓ No emiet p c iesp jas vair k l mes meh niski.
- ✓ Atlikumus var not r t ar dr nu, kas sam rc ta aceton vai EVO-STIK Adhesive Cleaner.
- ✓ Vienm r veiciet testa t r šānu maz k redzam viet .

## UZGLAB ŠANA

- ✓ Uzglab t l dz 12 m nešiem ori n l , neatv rt iepakojum , v s un saus viet temperat r no +5°C to +25°C

## DROŠ BAS PAS KUMI UN IEROBEŽOJUMI

- **Nav piem rota:** Putuplastam (expanded polystyrene) vai plastific tam PVH (vinilam).
- **Nedr kst izmantot:** Uz bitumena virsm m vai to tuvum
- **Evo-Stik 528 nesavieno:** Poliolefinus, piem ram, polietil nu un polipropil nu
- L me nav piem rota savienojumiem, kur starp virsm m ir tikai punktveida kontakts.
- P ragra virsmu savienošāna (pirms t s ir sausas) iesprostos š din t ju, kas var izrais t p š u veidošanos un v ju saiti.
- P ragra Virsmu savienošāna pirms t s k uvušas sausas uz tausti izrais s š din t ja iesprostošanu. Tas nelabv l gi ietekm s gal go savienojumu un var izrais t p š u veidošanos, jo paši tad, ja l me nav tikusi uzkl ta vienm r gi
- EVO-STIK 528 kontaktl me izveido savienojumu t l t ji, tikl dz abas virsmas saskaras. T d ir b tiski izvair ties no saskares, pirms deta as ir prec zi sal gotas, piem ram, ievietojot tapas gar vienas virsmas malu, pret kur m var atbalst t un prec zi novietot otru virsmu

## IEPAKOJUMS

Produktu kodi	30803761	500ml x 24 bundžas
	30803762	1L x 12 bundžas
	30813330	2.5L x 1 bundža
	30021180	5L x 1 bundža

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>

#### DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd  
Common Road,  
Stafford, ST16 3EH, UK  
Phone: +44 (0)1785 272625  
[www.bostik.com/uk](http://www.bostik.com/uk)

**BOSTIK HOTLINE**

Smart help +44 (0)1785 272625

