



# BOSTIK GENERAL PURPOSE AEROSOL

## SOLVENT BORNE, SPRAYABLE ADHESIVE IN AN AEROSOL CAN

TECHNICAL SHEET NO: TDS01345 09/03/2026

### SMART ADVANTAGES

- Excellent adhesion to most smooth porous or non-porous lightweight materials
- Fast drying
- Instant bond on contact

### DESCRIPTION

Bostik General Purpose Aerosol is a solvent borne, pressure sensitive, aerosol-based adhesive that is quick and easy to apply. It is designed for bonding lightweight sheet materials including foam, cork, felt and many other materials.

Bostik General Purpose Aerosol is fast drying and can be easily applied direct from the can. Using the adjustable spray nozzle provides a strong, flexible bond for many applications where a conventional adhesive would be too difficult to apply.



### APPLICATION

**IMPORTANT:** Before using Bostik General Purpose Aerosol refer to the relevant Health & Safety Data Sheet, available at [www.bostik.co.uk](http://www.bostik.co.uk).

### PREPARATION

- Work in warm but well-ventilated conditions.
- Make sure surfaces are dry, clean, and free from dust, dirt, and grease.
- Work on protected surfaces to guard against overspray.

### APPLICATION

- Shake the can well before use. Use the adjustable nozzle to select the required spray pattern.
- Bostik General Purpose Aerosol should be applied directly from the can onto the surfaces to be bonded.
- Hold the can 15 – 20 cm away from the surfaces to be sprayed and ensure that an even coat is applied to both surfaces.
- Allow the adhesive to become tacky (1 to 3 minutes) and then press the two surfaces together firmly. Some very porous surfaces may require two coats and drying time may be longer.

### TECHNICAL CHARACTERISTICS

<b>Colour</b>	Light Amber
<b>Form</b>	Liquid Aerosol
<b>Specific Gravity</b>	0.9 approx.
<b>Composition</b>	Adhesive solution in hydrocarbon solvents and propellant gas under pressure.
<b>Application Temperature</b>	-20°C to +60°C
<b>Drying Times</b>	Tack development: 1 to 3 minutes.  Full bond strength achieved in 15 to 25 minutes.
<b>Coverage (approx.)</b>	500ml can: 10-12m <sup>2</sup> per unit, depending on the nozzle setting and application technique

- Take care with woven fabrics not to apply too much adhesive or bond too early as excess adhesive could be forced through the fabric.
- After use, invert can and expel a small amount of propellant to clear nozzle.
- For thick heavy materials such as carpets and cork check the material is bedded down securely after 2 hours.

#### CLEANING

- Excess adhesive may be cleaned off with white spirit.
- Please test sensitive surfaces on a hidden area before cleaning.

#### STORAGE

- Store for up to 12 months when stored in original, unopened packaging under cool dry conditions within the temperature range of +5°C to +25°C.
- Protect from frost

#### PRECAUTIONS IN USE

Do not use on plasticised (soft flexible) pvc or vinyl tiles, due to plasticiser migration.

Not suitable for polystyrene and solvent sensitive surfaces. Do not use on asphalt or bituminous materials.

For any application not covered contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.co.uk](http://www.bostik.co.uk)

Recommendations and suggestions are for guidance only since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik General Purpose Aerosol, available at [www.bostik.co.uk](http://www.bostik.co.uk)

#### PACKAGING

<b>Product codes</b>	30811853	500ml x 12 cans
----------------------	----------	-----------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>

#### DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

**Bostik Ltd**  
Common Road,  
Stafford, ST16 3EH, UK  
Phone: +44 (0)1785 272625  
[www.bostik.com/uk](http://www.bostik.com/uk)

**BOSTIK HOTLINE**

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.